HTD-6330N/NS-Z100(S)

Stepping/Servo Series Multi-Application Platform


H.O.T

Product Description:





Specifications:



Platfom Features :

Servo Desktop platform

• Servo Motor + Ball Screw Transmission
• Higher precision; Larger capacity; Richer applications

Stepper Desktop platform

• Stepper Motor + Synchronous Belt Transmission
• Rich Optional Expansion Modules

Composition :

• 4-Axis Platform
• Handheld Control System
• Ball Screw
• Linear Guide
• MW Power Supply
• Servo/Stepper Motor
• Driver

Specifications:

Model:	HTD-6330NS-Z100S Servo Desktop Platform	HTD-6330N-Z100 Stepper Desktop Platform
Structure:	Dual Y Platform	Dual Y Platform
Working Range:	X600/$Y_1$300/$Y_2$300/Z100mm	X600/$Y_1$300/$Y_2$300/Z 100mm
Dimension:	L790*W534*H713mm	L790*W534*H713mm
Maximum Load:	X20kg/Y20kg/Z 15kg	X7kg/Y7kg/Z 5kg
Rapid Speed:	X/Y 500,Z200 mm/s	X/Y300,Z 200 mm/s
Transmission:	XYZ Axis: Servo Motor + Ball Screw	XYZ Axis: Stepper Motor + Synchronous Belt
Position Accuracy:	X/Y/Z±0.015mm	X/Y/Z±0.025mm
Program Capacity:	999 Program Files (65535 dots each)	999 Program Files (65535 dots each)
Control System:	Liquid Crystal Panel + Handheld Program Controller	Liquid Crystal Panel +Handheld Program Controller
Port Expansion:	Standard 1 Input / 4 Output; Expanded 10 Input / 10 Output	Standard 1 Input / 4 Output; Expanded 10 Input / 10 Output
Power Supply:	AC220V 50/60Hz 1.2kw	AC220V50/60Hz 1.2kw
Operating Environment:	20-90%RH, 0-40℃	20-90%RH, 0-40℃C
Weight:	Approx. 65kg	Approx. 65kg

Hotwin Technology Co.,Ltd

Website: www.hotwintech.com E-mail: sales@hotwintech.com Tel: +86 755-2919 8013