
HTV-PI02/HTV-PI03
Piezoelectric Injection Valve


H.O.T

Product Description:





Partial disassembly diagram of the liquid box:



Specifications:


Weight:	400g
Fluid Viscosity:	0 ~ 200000 cps
Fluid Type:	Underfill, UV adhesive, epoxy adhesive, silicone, red glue, etc.
Plunger Material:	Tungsten steel, ceramic, diamond
Nozzle Material:	Tungsten steel, ceramic, diamond
Seal Ring Materia:	PE, fluororubber
Plunger Models:	Tip diameter 0.5~2.7
Nozzle Models:	5-0.03~5-0.6

Feature:


- Adopts a fast top calibration method. No need calibration after cleaning and maintenance, shortening adjustment time.
- Original jetting mechanism with delicate modular design.
- 5mm nozzles, covering complete specifications.
- Low consumption parts, only one sealing ring needs regular replacement.

Product Description:





Partial disassembly diagram of the liquid box:



Specifications:

Weight:	550g
Fluid Type:	30CC Hot melt adhesive
Plunger Material:	Tungsten steel, ceramic, diamond
Nozzle Material:	Tungsten steel, ceramic, diamond
Seal Ring Material:	PEEK (high temperature & corrosion resistant), fluororubber
Plunger Model:	Tip diameter 0.5~2.7
Nozzle Model:	5-0.03 ~ 5-0.6

Feature:

- Equipped with modular 30cc heating barrel and compact adapter clamping assembly to save installation space.
- Adopts a fast top calibration method. No need calibration after cleaning and maintenance, shortening adjustment time.
- 5mm nozzles, covering complete specifications.
- Low consumption parts, only one sealing ring needs regular replacement.

Hotwin Technology Co.,Ltd

Website: www.hotwintech.com E-mail: sales@hotwintech.com Tel: +86 755-2919 8013