HT-IL6000B
In-line Soldering Robot

H.O.T

Product Description:



Product Features:

- Double Solder Station,improve space & efficiency.
- Real-time temperature monitor.
- Customized Multi-feed solderwire module.
- Anti-collision to avoid product damaged.
- 1D/2D barcode scanned via CCD.
- CCD Vision locate system.
- User friendly and easy-to-use programming.

Equipment Parameters:

Model	HT-IL6000B
Dimension	850*1100*1750mm
Travel Range	400*500*100mm* 360°
Product Max.Size	400*400mm
Motion Control Mode	IPC
Drive Mode	Servo Motor
Number of Axis	4 Axes
Segment Of Conveyor	2/3 Segments
Line Width	50-400mm
Maximum Load	10KG
Static Temperature Accuracy	±1℃
Repeat Position Accuracy	±0.02mm
Temperature Range	50-500/250-500℃
Maximum Move Speed	600mm/s
Tin Wire Diameter	Breaking Tin:(0.6-2.0mm) Feeding Tin:(0.3-2.0mm)
Average Power Consumption	185-265V/600W
Power	400W; Heating Core: 600W 200W; Heating Core: 500W
Weight	480KG

Hotwin Technology Co.,Ltd

Website: www.hotwintech.com E-mail: sales@hotwintech.com Tel: +86 755-2919 8013