HT-SEL3000C
Selective Wave Soldering Machine

H.O.T

Product Description:



Product Features:

- 3-Station: Spray + Preheat + Soldering
- Single/Double Solder Pot.
- Modular System .
- Multi-Point Real-Time Temperature Measurement .
- 5-Minute Rapid Programming.
- Zero-Hassle Nozzle Replacement.

Equipment Parameters:

Model	HT-SEL3000C
Dimension	2400*1600*1750mm
Power Consumption	380VAC/24KW
Operating Power	2.5-3KW
Weight	1500KG
Width	100-500mm
Height	900±20mm
Travel Axis	(Single Solder Pot):X,Y,Z_1 (Double Solder):X,Y,Z1,Z_2
Spray type	(Spot/Line Spraying)
Preheat Method	(Air+lnfrared)
Preheat temp	25-250℃
Wave Drive Method	(Mechanical Pump)/ (Electromagnetic Pump)(optional)
Capacity	15KG
Temprature	350℃
Melt Time	(Mechanical Pump)≤30mins (Electromagnetic Pump)≤75mins
Flux Capacity	2L

Alcohol Capacity	2L
Number of Solder Pots	(Optional)
High-definition online real-time monitoring	(Standard)
MaxPCB Size	500*500mm
PCB Thickness	0.2-6mm
PCBAmax.Weight	(Max)15Kg/(Customizable)
PCBA Height (Topside)	(Max)100mm
PCBA Height (Bottom Side)	(Max)60mm
PCB edge width	≥5mm
Programming	Panoramic Image/ Real-time Image/ Manual Programming
Barcodescan	CCD Scanning

Hotwin Technology Co.,Ltd

Website: www.hotwintech.com E-mail: sales@hotwintech.com Tel: +86 755-2919 8013